



104M

1:4 MICROPHONE AMPLIFIER/DISTRIBUTION AMPLIFIER



DESCRIPTION

- Level (Gain) Control.
- S/N Ratio - 78dB.
- Compact Size - Part of the Kramer TOOLS™ family of compact, high quality and cost effective solutions.

SPECIFICATIONS

INPUT:

One mono microphone 5mVpp/10kΩ on a 6.5mm phone connector.

OUTPUTS:

4 mono line level 1Vpp/150Ω on 6.5mm phone connectors.

MAX. OUTPUT LEVEL:

4.8 Vpp.

AUDIO BANDWIDTH (-3DB):

37kHz.

GAIN CONTROL:

5dB to 54dB.

S/N RATIO:

78dB.

THD @ 1KHZ:

0.1%.

POWER SOURCE:

12 VDC, 20mA.

DIMENSIONS:

12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98", W, D, H).

WEIGHT:

0.28 kg. (0.62 lbs.) approx.

ACCESSORIES:

Power supply, mounting bracket.

OPTIONS:

VA-50P power supply with six 12VDC outlets. RK-T1, RK-T3 rack adapters.

The Kramer 104M is a high quality distribution amplifier for dynamic microphone signals. It takes a microphone input and distributes the signal to four identical line-level outputs.

