



VP-501xI

COMPUTER GRAPHICS VIDEO SCAN CONVERTER



DESCRIPTION

- Input Compatibility - up to 1600 x 1200.
- Auto Set Up Technology - One button auto setup that automatically sizes, shifts, and centers any input image on the display device.
- Proc-Amp - Color, hue, sharpness, contrast, and brightness controls.
- Multi-Standard Output - PAL or NTSC (selectable).
- Multi-Format Output - Composite video and s-Video (Y/C) simultaneously.
- Control - Front panel with on screen display.
- Flicker Reduction.
- Over Scan or Under Scan (selectable) with LED indicator.
- Freeze Frame with LED indicator.
- Compact Size - Part of the Kramer TOOLS™ family of compact, high quality and cost effective solutions.

SPECIFICATIONS

INPUT:	1 x VGA/SVGA/XGA/UXGA on an HD15F connector.
OUTPUTS:	1 composite video 1Vpp/75Ω on a BNC connector. 1 Y/C (s-Video) 1Vpp/75Ω (Y), 0.3Vpp/75Ω (C) on a 4p connector.
OUTPUT STANDARDS:	PAL, NTSC (user-selectable).
MAX. OUTPUT LEVEL:	1Vpp.
S/N RATIO:	49dB.
CONTROLS:	Front panel and OSD: ProcAmp video controls, Freeze, Underscan/Overscan, Auto-image, 8 color bars.
POWER SOURCE:	12VDC, 270mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98", W, D, H).
WEIGHT:	0.3kg (0.67lbs) approx.
ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	19" rack adapters RK-T1, RK-T3.

The VP-501xI is a scan converter for computer graphics video signals. It converts computer graphics video signals up to UXGA (1600 x 1200) to composite and s-Video (Y/C) signals simultaneously in either PAL or NTSC formats.

