ConferenceSHOT ePTZ Camera SKU: 999-21050-001



The ConferenceSHOT ePTZ auto-framing camera for videoconferencing makes collaborating easy. Vaddio's ConferenceSHOT ePTZ delivers a dynamic, hands-free video experience that recreates the one-to-one videoconference experience perfect for hybrid working environments. The unique custom settings included with the camera make it ideal for enterprises that want professional-quality video for various meeting room environments.

Key Features:

- Intelligent Framing algorithms keep your participants in view
- 5x zoom with a 129° horizontal field of view
- Simultaneous USB 3.0, HDMI and H.264 IP Streaming(RTSP or RTMP)
- Integrated omnidirectional microphone with builtin Acoustic Echo Cancellation (AEC)
- Balanced audio line in and out
- * Three custom settings for auto-framing sensitivity and ability to mask high-traffic areas from auto-framer
- * Free Vaddio Deployment Tool for remote management, updates and more

The ConferenceSHOT ePTZ USB camera has a wide 129° field of view, making it perfect for small collaboration rooms and huddle spaces. The small camera is equally suited to areas where employees are socially distant, and you want to ensure everyone is in view. The built-in microphone is a convenient feature when mounting the ConferenceSHOT ePTZ on mobile display carts or in huddle rooms. Upgrade your old PTZ cameras and use existing room audio systems with the audio I/O ports located on the bottom of the camera –

a budget-friendly solution for updating outdated meeting rooms.

When setting up the camera, select one of three primary settings for how sensitive you want the camera auto-framing to be.

Conservative Conference is designed for low-motion environments, where little tracking action is needed. This mode is perfect for locations with glass walls or near busy walkways with visual background noise. Responsive Conference is the perfect option when you have teams that utilize the whole room – like collaborating on whiteboards or brainstorming at flipcharts and want their remote colleagues to stay right with the action. This mode quickly adjusts the image to include people entering and exiting the meeting space.

Default Conference is the sweet spot where most teams are happy with the system performance. The camera comes with a wall mount that allows the camera to tilt up and down to ensure proper framing of the conference table. The camera has a USB 3.0 Type C port, HDMI and audio I/O to easily integrate with existing room audio systems. The camera also has built-in RTSP and RTMP streaming capabilities for one-button streaming to popular services like YouTube, Facebook, Twitch, Vimeo and more.

The ConferenceSHOT ePTZ auto-framing camera is a simple plug-and-play video and audio peripheral with popular conferencing clients like Microsoft Teams, Zoom, and Google Meet. It is a professional camera at heart. At Vaddio, we pride ourselves on our superior image and product quality, custom control settings, and free remote management. AV and IT managers love the option of customizing camera performance for different environments and meeting types, mass firmware updates, video stream preview for troubleshooting, and free local technical support without any service contracts.



Vaddio Deployment Tool

conference rooms with the free desktop application. Download Now

This Package Includes:

- * ConferenceSHOT ePTZ Camera
- * Wall mount and mounting hardware
- [°] Cable cover
- ^o 6 ft (1.8 m) USB 3.0 cable, type C to A
- PoE power injector
- * Vaddio IR Remote
- [•] 3.3 ft (1 m) Cat-5e cable
- Quick-Start card

Specifications

Dimensions &

Measurements

Depth	2.17 in (5.5 cm)
Height	6.89 in (17.5 cm)
Operating Temperature	32° to 104°F (0° to 40°C)
Product Weight	1.95 lbs (0.9 kg)
Storage Temperature	32° to 104°F (0° - 40°C)
Width	4.72 in (12 cm)

Characteristics & Features

3rd Party Control	Telnet
Browser-based User Interface for Remote Control	Built-in
Camera Type	Fixed
Color	Black
Control Method	 Telnet Touch Screen Web UI
Estimated Room Size	Huddle Room Small Room
Field of View	129° Wide End to 25.8° Tele End

Fiel	Ы	of	\/i	۸۱۸	۱۸	/i	de
пе	IU.	OI	VII	₽w.	V V	ш	ue

Greater than 70

Focus System	• Auto • Manual
Gain	Auto Manual
Image Sensor Type	1/1.8-Type CMOS sensor
Input Ports	AudioNetworkUSB 3.0
Invertible	Yes
Manufacturer	Vaddio
Max Resolution	1080p30
Minimum Illumination	100 lux recommended
OneLINK Compatibility	No
Output Ports	AudioHDMIIP StreamingNetworkUSB 3.0 Type C
Pixels	8 Megapixel
Power Cord	EU Cord, UK Cord
Power Supply	PoE
Power Type	PoE
Preset Positions	16 Custom Home Position
Quick-Connect Compatibility	No
Signal Type	AudioHDMIIP StreamingUSB 2.0

		• USB 3.0
	Solution Type	Camera Only
	Special Features	Audio IO
		 Auto-Framing
	TAA Compliant	Yes
	Tri-Sync Motion	No
	White Balance	• Auto
		 Manual
		One Push
	Zoom	5x Digital Zoom
Certifications &	Certifications	• CE
Warranties		Certified for Barco
		ClickShare Conference
		• RoHS
		• TAA
		UL Listed
	Warranty	3 years

Source: https://www.legrandav.com/products/cameras/hd_fixed_camera/conferenceshot-eptz-camera/999-21050-001