

EasyIP 5 ePTZ Camera SKU: 999-30150-000





An HD ePTZ camera with IntelliFrame™ motion-based auto-framing that makes video conferencing and live streaming effortless.

Key Features:

- 5x zoom with 100° horizontal field of view
- One EasyIP (PoE+) network video output, plug-andplay with EasyIP endpoints
- * Customizable auto-framing for a variety of environments
- EasyIP Multicast enables video distribution to any number of EasyIP endpoints

The EasyIP 5 ePTZ camera has a wide 100° field of view, making it perfect for getting everyone in the frame in small collaboration rooms and huddle spaces. EasyIP 5 eliminates the need for costly USB extenders by sending 1080p resolution video feeds to EasyIP endpoints over category cables.

Use EasyIP 5 with endpoints like the EasyIP Decoder for a USB output that connects you with your favorite conferencing software like Microsoft Teams, Google Meet and Zoom. Integrate the EasyIP 5 with existing video and audio systems and gain useful features like picture-in-picture and graphic overlays using the EasyIP Mixer.

Offering superior flexibility for various environments, installers can select one of three primary settings for how sensitive you want the camera's auto-framing to be. Conservative Conference is designed for low-motion environments, Responsive Conference is the perfect option when you have teams that utilize the whole room, and Default Conference is the sweet spot where most teams are happy with the system performance.

An included Wall Mount Bracket allows the camera to tilt up and down to ensure proper framing of the conference table or room. Additional ceiling and ondisplay mounts are available separately.



Vaddio Deployment Tool

Easily deploy and manage hundreds of Vaddio devices with the free desktop application. Download Now

This Package Includes:

- [•] EasylP 5 ePTZ Camera
- * Wall mount with tilting feature and mounting hardware
- [°] Cable cover
- Vaddio IR Remote Master
- 3.3 ft (1 m) cat-5e snagless cable
- [•] Quick-start card

Training

Discover the power of EasyIP and revolutionize your AV setup. This course dives into the essentials of AV over IP, showcasing how EasyIP simplifies your installations and enhances your conferencing experiences. Enroll in this course in AV University

Specifications

Dimensions &	Depth	2.17 in (5.5 cm)
Measurements	Height	6.89 in (17.5 cm)
	Operating Temperature	32° to 104°F (0° to 40°C)
	Product Weight	1.95 lbs (0.9 kg)
	Shipping Dimensions	14" x 14" x 18" (355.6 x 355.6 x 457.2 mm)
	Shipping Weight	13 lbs (5.9 kg)
	Storage Temperature	32° to 104°F (0° - 40°C)
	Width	4.72 in (12 cm)
Characteristics & Features	Browser-based User Interface for Remote Control	Built-in
	Camera Type	Fixed
	Color	Black
	Control Method	Touch ScreenWeb UI
	Estimated Room Size	 Huddle Room Large Room Small Room
	Field of View Wide	Greater than 70
	Focus System	Auto Manual
	Gain	Auto Manual
	Image Sensor Type	1/1.8-Type CMOS sensor
	Input Ports	Network

Invertible	Yes	
Manufacturer	Vaddio	
Max Resolution	1080p30	
Minimum Illumination	100 lux recommended	
OneLINK Compatibility	No	
Output Ports	Network	
Pixels	8 Megapixel	
Power Supply	PoE	
Power Type	PoE	
Preset Positions	16 Custom Home Position	
Quick-Connect Compatibility	No	
Signal Type	EasylP	
Solution Type	Camera Only	
Special Features	Auto-Framing	
TAA Compliant	Yes	
Tri-Sync Motion	No	
UPC	840077508197	
White Balance	AutoManualOne Push	
Zoom	5x Digital Zoom	
Certifications	• CE • FCC • RoHS	

Certifications & Warranties

 RoHS • TAA

Warrantv 3 vears Trainenty 5 years

Source: https://www.legrandav.com/products/cameras/av_over_ip/easyip-5-eptz-camera/999-30150-000