legrand® | AV

EasyIP 20 Base Kit with Professional IP PTZ Camera **SKU: 999-30232-001**

The EasyIP 20 Base Kit is an AV-over-IP professional PTZ camera system in a box. It delivers professional image quality for UC soft clients and simplifies the BYOD (bring your own device) conferencing experience by moving videoconferencing onto the network.

This networked video capturing system allows you to use up to four PTZ cameras in your meeting room, without needing a video switch. It's a simple AV-over-IP solution for extended and networked video capture and streaming in medium and large spaces.

The EasyIP 20 Base Kit includes everything you need to get started with AV-over-IP video in one easy-to-order bundle including one EasyIP 20 Camera, one EasyIP Decoder and one EasyIP Switch.

Key Features
- Designed for flexible configuration in medium and large rooms
- One EasyIP (Network PoE+) and one HDMI video output
- 20x zoom, Tri-Synchronous Motion, Enhanced Wide Dynamic Range
- Provides USB 3.0 connection to leading web services: Teams/Skype for Business, Zoom, WebEx, BlueJeans, Google Meet and others

The EasyIP 20 Base Kit is an AV-over-IP professional camera system in a box. It delivers professional image quality for UC soft clients and simplifies the BYOD (bring your own device) conferencing experience by moving videoconferencing onto the network.

The EasyIP 20 Base Kit includes everything you need to get started with AV-over-IP video capture and streaming in one easy-to-order bundle.

Vaddio Deployment Tool
Easily deploy and manage hundreds of conference rooms with the free desktop application. Download Now

This Package Includes:

- EasyIP 20 PTZ Camera (black or white)
- Thin Profile Wall Mount (black or white) with mounting hardware
- Vaddio IR Remote Commander
- EasyIP Switch
- Rack mount kit (for mounting the EasyIP Switch)
- EasyIP Decoder
- Half-Rack mounting kit (for mounting the EasyIP Decoder into a full rack space)
- 10 ft (3.05m) cat-5e snagless Cable, black
- 3 ft (0.91 m) cat-5e cable
- 6 ft (1.8 m) USB 3.0 cable
- 1 qty 4-position phoenix-style connector
- Power cord (for EasyIP Switch)
- Quick-start cards

Total Pixels: 2.14 Megapixel

Specifications

Dimensions & Measurements		
	Operating Temperature	32° to 104°F (0° to 40°C)

Characteristics & Features		
	Browser-based User Interface for Remote Control	Built-in
	Camera Type	PTZ
	Color	Black
	Control Method	• IR Remote • Joystick • RS232 • Telnet • Web UI
	Estimated Room Size	• Large Room • Medium Room
	Field of View	70.2° Wide End to 4.1° Tele End
	Field of View Wide	Greater than 70
	Focus System	• Auto • Manual

Gain	• Auto • Manual
Image Sensor Type	1 25 type Exmor R CMOS sensor
Invertible	Yes
Manufacturer	Vaddio
Max Resolution	1080p 60
Minimum Illumination	100 lux recommended
OneLINK Compatibility	No
Pan and Tilt Range	• Pan: ±150° • Tilt: +90° to -30°
Pan and Tilt Speed	0.35°/sec - 90°/sec
Pixels	2.14 Megapixel
Power Cord	EU Cord, UK Cord
Power Supply	PoE+
Preset Positions	16 Custom Home Position
PTZ Motors	Stepper Motors
Quick-Connect Compatibility	No
Signal Type	• EasyIP • HDMI • RS 232
Solution Type	Conference Room System
TAA Compliant	Yes
Tri-Sync Motion	Yes
UPC	840077506711
White Balance	• Auto • Manual • One Push

	Zoom	20x
Certifications & Warranties	Certifications	• CE • FCC • TAA
	Warranty	3 years