

## AV Bridge Nano **SKU: 999-82600-000**

---



A highly portable video capture and streaming device with conferencing capabilities for IT professionals.

### Key Features:

- Converts an HDMI source into plug-and-play USB and IP connections for use in soft-conferencing or streaming software
- Single device capable of USB or IP streaming (up to 1080p/60 quality with USB 3.0)
- Compact size, portable and perfect for under-table or behind-display mounting

### Request a Demo

Want to learn more about AV Bridge Nano?  
We'll connect you with a product expert to discuss your business needs and facilitate a product demo. [Request a Demo](#)

---

Building upon the success of the AV Bridge Mini and AV Bridge 2x1, the AV Bridge Nano is a brand-new addition to the product family known for its ability to connect professional AV equipment to USB and IP streaming applications. It retains some of the most popular qualities of the full-featured AV Bridge models in a highly portable, cost-effective device that IT and enterprise users will appreciate. The AV Bridge Nano also complements AV systems in lecture halls, town hall meetings, or houses of worship.

The AV Bridge Nano enables reliable streaming and video capture scenarios over USB or RTSP/RTMP without needing to purchase two separate devices. The essential feature set makes it ideal for the corporate user in cost-conscious applications that do not require the full functionality of the AV Bridge Mini. It is fully compatible with the Vaddio Deployment Tool and Vaddio Device Controller touchscreen accessory, and the HDMI pass-through feature makes it easy to integrate into Cisco codec setups.

The AV Bridge Nano is compatible with the most popular soft conferencing applications, such as Microsoft Teams, Zoom, WebEx and others, thanks to its powerful USB 3.0 interface. It can also be used as a USB capture card for ingesting HDMI video into video editing applications like Adobe Premiere and OBS Studio. Its networking capabilities enable the creation of production-quality live streams on platforms such as YouTube Live, LinkedIn, Facebook, Twitch, Dacast and Panopto.

The smallest chassis in the Vaddio AV Bridge lineup ensures ultimate portability and allows the AV Bridge Nano to be mounted under a table, behind a display, or within a mobile conferencing cart system with the optional table-mount. The Kensington lock port provides peace of mind.

Note: Installers looking for simultaneous USB and IP streaming, PoE power, rack-mounting or more full-featured conference/meeting room solutions should consider AV Bridge Mini or AV Bridge 2x1.



#### **Vaddio Deployment Tool**

Easily deploy and manage hundreds of rooms with the free desktop application.

[Download Now](#)

---

#### **This Package Includes:**

- AV Bridge Nano
- 12V power supply with international adapter plugs
- 3 ft. (0.9m) USB 3.0 cable, type C to A

# Specifications

## Dimensions &

## Measurements

Depth	4.43 in (11.3 cm)
Height	1.27 in (3.2 cm)
Operating Temperature	32° to 104°F (0° to 40°C)
Product Weight	1.6 lbs (0.7 kg)
Shipping Dimensions	8.75" x 6.125" x 2.75" (222.3 x 155.6 x 69.9 mm)
Shipping Weight	3 lbs (1.4 kg)
Width	5.83 in (14.8 cm)

Characteristics &  
Features

Browser-based User Interface for Remote Control	Built-in
Color	Black
Control Method	<ul style="list-style-type: none"><li>• Telnet</li><li>• Web UI</li></ul>
Input Ports	<ul style="list-style-type: none"><li>• 3.5mm stereo Line Level Audio</li><li>• HDMI</li><li>• RJ-45</li></ul>
Max Resolution	1080p 60
OneLINK Compatibility	No
Output Ports	<ul style="list-style-type: none"><li>• Audio</li><li>• Audio</li><li>• HDMI</li><li>• HDMI</li><li>• IP Streaming</li><li>• IP Streaming</li><li>• USB 3.0 Type C, uncompressed USB 3.0, MJPEG compression on USB 2.0</li><li>• USB 3.0 Type C, uncompressed USB 3.0, MJPEG compression on USB 2.0</li></ul>
Power Supply	<ul style="list-style-type: none"><li>• 1.5</li><li>• 12VDC</li></ul>
Power Type	Local Power
Special Features	<ul style="list-style-type: none"><li>• IP Streaming</li><li>• Kensington Lock</li></ul>
TAA Compliant	Yes
UPC	840077508104

**Certifications &  
Warranties**

Certifications

- CE
- FCC
- TAA

Warranty

3 years

Source: [https://www.legrandav.com/products/av\\_to\\_usb\\_bridges/av\\_bridge/av-bridge-nano/999-82600-000](https://www.legrandav.com/products/av_to_usb_bridges/av_bridge/av-bridge-nano/999-82600-000)