CLS-GM/GM

15-pin HD Cable - Low Smoke & Halogen Free

| VGA/UXGA - 15-pin HD

Kramer's CLS-GM/GM computer graphics video cable is a high-performance cable with molded 15-pin HD connectors on both ends. It is used for connecting computer graphics video signals between computers or video scalers and plasma, LCD or other popular display technologies. DDC2 is supported. The CLS Series is low smoke and halogen free

FEATURES

- Quality Construction - Highresolution 26AWG mini coax for video
- Easy Installation - Preterminated with molded 15pin HD connectors, goldplated pins and thumbscrews for easy connection
- All 15 Pins Connected
- Low Smoke, Halogen Free
- Varied Selection of Lengths - Available in versions of 0.9 to 15m (3, 6, 10, 12, 15, 25, 35 and 50ft)

TECHNICAL SPECIFICATIONS

CONSTRUCTION	
Dielectric:	Foam polyethylene with red, green, blue color coding
Shield:	(A) 90% spiral 38 AWG tinned copper. (B) aluminumfoil/Mylar 25% overlap rate
Inner Jacket:	PVC
Jacket Colors:	Black
DIAMETERS	
Dielectric:	0.076in (1.95mm)
Individual Coax:	0.102in (2.6mm)
ELECTRICAL	
DC resistance:	45/1000ft (148/km)
Capacitance:	17.3pF/ft (57pF/m)
Temperature:	68° to 167°F (20° to 75°C)
Attenuation (dB/100 ft.):	0.5dB @1MHz 1.3dB @5MHz 1.9dB @10MHz 4.0dB @50MHz 5.7dB @100MHz 8.0dB @180MHz 14.0dB @400MHz
REGULATORY	
CSA:	C(UL) CL2
EN:	Low Smoke Halogen Free according to: EN 502651:1998 EN 5026521:1998 EN 5026721:1998 EN 5026722:1998

CONFIGURATIONS

CLS-GM/GM-3	Molded 15-pin HD (M) to 15-pin HD (M) Cable
CLS-GM/GM-6	Molded 15-pin HD (M) to 15-pin HD (M) Cable
CLS-GM/GM-10	Molded 15-pin HD (M) to 15-pin HD (M) Cable
CLS-GM/GM-15	Molded 15-pin HD (M) to 15-pin HD (M) Cable
CLS-GM/GM-25	Molded 15-pin HD (M) to 15-pin HD (M) Cable
CLS-GM/GM-35	Molded 15-pin HD (M) to 15-pin HD (M) Cable
CLS-GM/GM-50	Molded 15-pin HD (M) to 15-pin HD (M) Cable