

VP-14xI

RS-232 Port Extender/Converter



The VP-14xl is a port extender for RS-232, RS-485 or USB command signals. The unit converts the incoming commands to three RS-232 outputs

FEATURES

Hardware or Software Mode Operation

DIP-Switch Controls - For HW source, SW addressing and baud rate



TECHNICAL SPECIFICATIONS

INPUT: 1 RS232 on 9pin Dsub (F) connector; 1 RS485 on 3pin removable terminal block;

1 USB Type B connector

OUTPUTS: 2 RS232 on 9pin Dsub (M) connectors, 1 RS232 on 3pin removable terminal block

BAUD RATE: 1200 to 115200bps

OPERATING MODES: Hardware and software

USB COMPLIANCE: 1.1

CONTROLS: DIPswitches

POWER 5V DC, 130mA

CONSUMPTION:

INCLUDED Power supply, mounting bracket

ACCESSORIES:

PRODUCT 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

DIMENSION:

SHIPPING WEIGHT: 0.6kg (1.2lbs) approx

OPTIONS: RK3T 19" rack adapter

