

## VS-211HDxI

2x1:2 3G HD-SDI Automatic Standby Switcher

| 3G HD-SDI - BNC



The VS-211HDxl is a high-performance automatic switcher for 3G HD-SDI video signals. When configured as a standby switcher, it switches to the secondary input when the primary input is lost

## **FEATURES**

Max. Data Rate - 3Gbps

Multi-Standard Operation - SDI (SMPTE 259M and SMPTE 344M), HDSDI (SMPTE 292M) & 3G HDSDI (SMPTE 424M)

**HDTV** Compatible

Control - Contact closure or automatic switching

Automatic Standby Switching - Switches from the secondary input to the primary input when a primary signal is detected

Primary Input - Selectable

Active Input LED Indicators

Compact DigiTOOLS™ - 3 units can be rack mounted sidebyside in a 1U rack space with the optional RK3T rack adapter



## TECHNICAL SPECIFICATIONS

INPUTS: 2 SD/HD/3G HDSDI video on BNC connectors

OUTPUTS: 2 SD/HD/3G HDSDI video on BNC connectors

MAX. OUTPUT

LEVEL:

800mVpp/75

DATA RATE: Up to 2.97Gbps

CONTROLS: Contact closure remote control, input default selection switch

COUPLING: AC

POWER 5V

CONSUMPTION:

5V DC, 400mA

INCLUDED

ACCESSORIES:

Power supply, mounting bracket

OPTIONS: RK3T 19" rack adapter

·

PRODUCT DIMENSION:

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96" ) W, D, H

PRODUCT WEIGHT: 0.2kg (0.4lbs) approx

SHIPPING DIMENSION:

23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H

SHIPPING WEIGHT: 0.6kg (1.3lbs) approx

