



Temperature Sensor 7000
(RJ11 plug)



Temperature Sensor 7001
(mini-DIN plug, IP64)



Temp., Humidity Sensor 7002
(mini-DIN plug)



Temperature Sensor 7101
(RJ45 plug, IP64)

Order Code	Product	Feature	Compatible to
7000	Temperature Sensor 7000	Cable sensor, RJ11 connector, -20°C to +80°C, cable length ca. 2.3 m	Expert Power Control 8090 EMC Professional 3011
7001	Temperature Sensor 7001	Cable sensor with splash-proof sensor head (IP64), Mini-DIN connector, -20°C to +80°C, cable length ca. 2.3 m	Expert Power Control 1202, 1292, Expert Net Control 2312
7002	Temp., Humidity Sensor 7002	Cable sensor, Mini-DIN connector, -20°C to +80°C, 0-90% humidity, cable length ca. 2.3 m	as for 7001
7101	Temperature Sensor 7101	Cable sensor with splash-proof sensor head (IP64), RJ45 connector, -20°C to +80°C, cable length ca. 2.3 m	Expert Power Control 1104, 1105, 8021, 8031, 8041, 8221, 8226, 8314, 8316 Expert PDU Energy 8311, 8341 Expert Transfer Switch 8801 Expert Net Control 2111, 2191, 2302 Expert Sensor Box 7213, 7214

Accessories: Sensors



Temp., Humidity, Air pressure Sensor
7104, 7105, 7106 (RJ45 plug)



new

Calibrated Temp., Humidity, Air pressure Sensor
7104-2, 7105-2, 7106-2 (RJ45 plug)



Temperature Sensor 7201 (RJ45 socket)
Temp., Humidity Sensor 7202



Smoke Detector 7311, 7312



Leakage Point Sensor 7313

Order Code	Product	Feature	Compatible to
7104	Temperature Sensor 7104	Cable sensor, RJ45 connector, -20°C to +80°C, cable length ca. 2.3 m	Expert Power Control 1104, 1105, 8021, 8031, 8041, 8221, 8226, 8314, 8316 Expert PDU Energy 8311, 8341 Expert Transfer Switch 8801 Expert Net Control 2111, 2191, 2302 Expert Sensor Box 7213, 7214
7105	Temp., Humidity Sensor 7105	Cable sensor, RJ45 connector, -20°C to +80°C, 0-90% humidity, cable length ca. 2.3 m	as for 7104
7106	Temp., Humidity, Air pressure Sensor 7106	Cable sensor, RJ45 connector, 20°C to +80°C, 0-90% humidity, 300-1100 hPa, cable length ca. 2.3 m	as for 7104
7104-2	Temperature Sensor 7104-2	Cable sensor with calibrated temperature range , RJ45 connector, -20°C to +80°C, cable length ca. 2.3 m	as for 7104
7105-2	Temp., Humidity Sensor 7105-2	Cable sensor with calibrated temperature range , RJ45 connector, -20°C to +80°C, 0-90% humidity, cable length ca. 2.3 m	as for 7104
7106-2	Temp., Humidity, Air pressure Sensor 7106-2	Cable sensor with calibrated temperature range , RJ45 connector, 20°C to +80°C, 0-90% humidity, 300-1100 hPa, cable length ca. 2.3 m	as for 7104
7201	Temperature Sensor 7201	Box case with RJ45 socket, -20°C to +80°C	as for 7104
7202	Temp., Humidity Sensor 7202	Box case with RJ45 socket, -20°C to +80°C, 0-90% humidity	as for 7104
7311	Optical Smoke Detector 7311	Overhead installation (d=100 mm), screw terminal NO or NC	Expert Net Control 2111, 2191, 2302 Expert Sensor Box 7214
7312	Thermal Smoke Detector 7312	Overhead installation (d=100 mm), screw terminal NO or NC	as for 7311
7313	Leakage Point Sensor 7313	13 mm two-tined, detects flooding, operation by 12 V, 4-core cable (2.5 m)	as for 7311